

LKV373KVM Specification

| Part No. | LKV373KVM | |
|---|---|---|
| Technical | Transmitter-TX | Receiver-RX |
| Signal format | HDMI | |
| HDMI connector | Type A ,19 pin, Female | |
| Transmission distance | CAT5/80 meters, CAT5e/100meters, CAT6/120 meters | |
| LAN connector | RJ-45 | |
| Video bandwidth | ≤70Mbps | |
| resistance | 75Ω | |
| Video Latency | 70 ms | |
| Supported OS and version | Windows 7, Windows 7 x64, Windows Server 2008, Windows Server 2008 x64, Windows Vista, Windows Vista x64, Windows Server 2003, Windows XP, Windows XP-x64, Windows 2000, Windows ME, Windows 98SE | |
| HDMI resolution supported | 640*480@60Hz 800*600@60Hz 1024*768@60Hz 1280*720@60Hz 1360*768@60Hz 1440*900@60Hz 1400*1050@60Hz 1680*1050@60Hz 1920*1080@60Hz | |
| Audio support | PCM (44.1KHz, 48KHz) | |
| KVM function (connect with PC、keyboard/mouse) | connect with PC | connect with keyboard/mouse |
| Switch Connection | yes | |
| Input | 1×HDMI 1xUSB(to connect with PC) | 2xUSB(to connect with keyboard/mouse) 1×RJ45 |
| Output | 1×RJ45 | 1×HDMI |
| Mechanical | Transmitter-TX | Receiver-RX |
| Housing | Metal enclosure | |
| Dimension | 109.6(L)x89.5(w)x26.3(H)mm | |
| Net weight | 160g | 170g |
| Power supply | DC5V 1A | |
| Power consumption | <3.5W | <3.5W |
| Operation temperaure | 0-60℃ | |
| Storage temperature | —20-70℃ | |
| Relative humidity | 20-90% (no condensation) | |